



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport2, 75Nm, PedalPlus 6-sensor technology
BEDIENINGSUNIT	Giant RideControl Ergo 2 remote, Smart Assist automatic mode, 5 support levels, USB-C (10W)
DISPLAY	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
ACCU	Giant EnergyPak 625Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production
LADER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
MATEN	S, M, L, XL
KLEUREN	Pyrite Brown / Black
FRAME	ALUXX SL aluminum, Integrated battery design, Headset integrated cable routing, M10 Trailer Mount, 27,5" Frame-set, KSA40 Kickstand
VOORVORK	SR Suntour XCR32 ATB LO 27.5" Coil 100mm
DEMPER	n/a
ONDERDELEN	
STUUR	Giant Contour Comfort Riser 31.8x690mm
HANDVATTEN	Giant Comfort Ergo Microtech Plus Lock-on
STUURPEN	Giant Contour, EVO integrated, high adjustable
ZADELPEN	Suspension dropper post, handlebar operated remote control, 30.9mm
ZADEL	Selle Royal Vivo Ergo Unisex
PEDALEN	VP VPE537, PP platform / Anti-slip
AFMONTAGE	
SHIFTERS	Shimano Deore 10-speed
VOORDERAILLEUR	n/a
ACHTERDERAILLEUR	Shimano Deore, 10-speed, Shadow+
REMMEN	Shimano BR-MT200, hydraulic disc, 180mm
REMHENDELS	Shimano BL-MT200
CASSETTE	Shimano Deore, CS-M4100, 11-46T, 10-speed
KETTING	KMC e.10 Sport, e-bike optimized
CRANKSET	Alluminum 42T
BOTTOM BRACKET	n/a

WIELSET	
VELGEN	Giant eX25, Tubeless Ready, 584x25 Aluminium
NAVEN	Shimano HB-MT200 100x9mm QR Disc [F] Shimano FH-QC400-HM [R]
SPAKEN	Stainless
BANDEN	Schwalbe Smart Sam Plus 57-584 (27.5 x 2.25"), DD, GreenGuard, ADDIX, E-50
EXTRA'S	KSA40 direct mount kickstand
ACCESSOIRES	
VERLICHTING	Giant Recon HL50, 50 lux [F]AXA Juno 6-12V E-bike tail light [R]
SLOT	ABUS Xplus Battery Lock / Abus 5755L XPlus R (ART certified)
DRAGER	MIK HD rack. System bag & basket compatible

Adviesprijs: € 3.799,00

GEOMETRIE

FRAME	S	M	L	XL
Zitbuis lengte (mm)	340	410	480	550
Zitbuis hoek	74,0°	73,0°	72,0°	72,0°
Frame Lengte (horizontaal) (mm)	570	590	610	630
Balhoofdbuis Lengte (mm)	130	130	170	170
Balhoofdbuis Hoek	69,5°	69,5°	69,5°	69,5°
Vork Sprong (mm)	44	44	44	44
Naloop (mm)	87	87	87	87
Wielbasis (mm)	1120	1128	1138	1158
Liggende achtervork lengte (mm)	470	470	470	470
Bottom Bracket Drop (mm)	50	50	50	50
Stack (mm)	625	625	662	662
Reach (mm)	391	399	395	415
Stand Over Height (mm)	592	564	524	488
Stuur breedte (mm)	690	690	690	690
Stuurpen Lengte (mm)	90	90	110	110
Cranklengte (mm)	170	170	170	170
Wielmaat	27.5"	27.5"	27.5"	27.5"

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.